



## Series 10 Gravimetric Filler

When filling gravimetrically, the All-Fill Series 10 fillers incorporate a weigh-cell or balance to provide the signal for the filling to stop, eliminating inaccuracies caused by products of inconsistent density.

Two-speed filling with high speed bulk and slow speed top-up or multi-stage filling provide even greater accuracy.



### Standard Features

- ▼ Weigh-cells/balances as appropriate
- ▼ Free-standing
- ▼ Semi-automatic
- ▼ All stainless-steel contact parts
- ▼ 56 litre stainless steel hopper
- ▼ No-tools removable change parts
- ▼ Auger machined from solid
- ▼ Servo-driven auger
- ▼ Independent agitation drive
- ▼ PLC control via touch-screen panel
- ▼ Siemens PLC-based weigh-fill controller

### Options

- ▼ 2-speed bulk fill and top up
- ▼ Bulk fill and feed forward
- ▼ Loss-in-weight filling
- ▼ Electro-pneumatic sack/bag clamps
- ▼ Product Recipe Memory
- ▼ Lean-Clean 56 litre Split Hopper
- ▼ Hopper Level Probe
- ▼ Bulk Feed Accessories
- ▼ Full stainless-steel specification
- ▼ 316L contact parts
- ▼ 38 litre stainless steel hopper

### All-Fill International Ltd

Unit 5 Gateshead Close | Sandy | Bedfordshire | SG19 1RS | United Kingdom

+44(0)1767 691100

info@allfill.co.uk

www.allfill.co.uk




# Series 10 Gravimetric Filler



## Standard Specification

Controller type:	Siemens PLC	Hopper capacity:	56 litres
HMI:	Colour touch-screen panel	Auger revs:	0.0003 rev incremental adjustment
Agitation drive:	0.55kW	Auger tooling:	Manufactured from solid steel
Agitation options:	Continuous	Contact parts:	304 grade stainless steel
	With fill only	Fill weight range:	1g – 25kg
	With fill and time delay	Power:	2.2 kva
	No agitation	Typical Weight:	185kg



All-Fill International Ltd

Unit 5 Gateshead Close | Sandy | Bedfordshire | SG19 1RS | United Kingdom

+44(0)1767 691100

info@allfill.co.uk

www.allfill.co.uk